



- COCL= Center of opening from cover left side
- COW = Clear opening width
Recom. (SBL-2xLAP-100)/1,5
Min. 1600, max. (SBL-2xLAP-G)/1,5
- CL = Cover length incl 2x30 mm end plates
Recom. (1,5xCOW) + (2xLAP) + 100 + (2X30)
Min. (1,5xCOW) + (2xLAP) + 60
- DH = Door leaf height
- SBL = Support beam length
Recom. (1,5xCOW) + (2xLAP) + 100
Min. (1,5xCOW) + (2xLAP), Max. 6100
- LAP = Overlapping
- G= Space between closed door leaves
- DW= Door width (If door adaptor state DW)
- K= Clear opening width, fixed screens

State when ordering

COCL=.....mm
 COW=.....mm
 Cover
 CL=.....mm
 SBL=.....mm
 LAP=.....mm
If not stated LAP = 20
 G=.....mm
If not stated G = 0
 DW=.....mm

Surface treatment

Silver anodized
 Special anodized.....
 RAL.....
 Special powder coating

Customer: _____
Door id: _____
Project No: _____

Ref: _____
Date: _____
Sign: _____

Sliding door operator
Entrematic EMSL T - 2
Article No. 500339

ENTREMATIC
4.0
833083